

Paste Blister Packing Machine DPP-80L



This machine is suitable for packing the liquid like chocolate, jam, butter, honey widely used in food industry.

Features

- 1. It adopts the newest type high-power transmission mechanism to arrange the chain and drive the main driving shaft. The errors and noises of other gear wheel transmission can be avoided.
- 2. Imported controlling system is adopted; also it can be equipped with detecting and rejection function device for number of medicines according to the user's requirement.
- 3. The machine adopts separation sectional combination: PVC forming, Feeding, Heating sealing for one section; Tropical cold aluminum forming, Heating sealing and cutting for another one section for separately packaging.
- 4. It can be optional equipped with photocell correction device, imported stepper motor traction and image-character register to optimize packing grade
- 5. It adopts photoelectrical controlling system to make PVC, PTP, be cut automatically to guarantee the Synchronous stability of over- length distance and multi stations.
- 6. All of working stations are adopted four columns for position. It is with stability performance and easy operation.
- 7. It can add pressing station. It can be with total of four working stations of forming, sealing, pressing and cutting. It is widely suitable for all requirements of packaging.
- 8. Feeding heading (Note: two feeding head can produce two version each time, but it depends on the size of customer' product, if it is too big, it will adapt one feeding head.)
- 9. Sample

Technical Parameter:

Model	DPP-80L
Punching frequency	10-35 Times/min.
Production capacity	2400 Pcs/H
Max.forming area, depth	70*110*26mm
Standard travel range	20-80mm
Standard blister size	80*57mm
Air supply	0.6-0.8Mpa
Total power	380V 50Hz 3.0Kw
Main motor power	0.75Kw
PVC sheet	Thickness (0.15-0.5)*Width80mm
PTP	Thickness (0.02-0.035)*80mm
Dialyzing paper	(50-100) g*80mm
Cooling mould	Running water, Circulation water
Overall dimension	1500*600*1200mm
Weight	450Kg
Noise	<75dBA