

## Sausage Preserved Fruit Packing Machine SK-250 (350/450/600/700)X



## Main performance and structure features:

- 1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films
- 2. Human-machine operation, convenient and quick parameter setting.
- 3. Self-diagnosis failure function, clear failure display.
- 4. High sensitivity optical electric color mark tracking &digital input cut position which makes the sealing&cutting more accurate.
- 5. Separate PID control to temperature, suitable for various packing materials.
- 6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
- 7. Simple driving system, reliable working, convenient maintenance.
- 8. All the controls are achieved by software, convenient for function adjusting and upgrading.

## **Application:**

This fruit packing machine is Be applicable for packaging of sticky and diffuse product suck such as towels, tissues, noodles, preserved fruit, haw slice, sausage, ect.

## Specification:

Model	SK-250X	SK-350X	SK-450X	SK-600X	SK-700X
Film width	250mm	350mm	450mm	600mm	700mm
Bag length	65-190mm or	65-190mm or	100-450mm	120-500mm	120-500mm
	100-300mm	100-400 mm			
Bag width	30-110mm	50-160mm	50-180mm	100-280mm	100-330mm
Product's height	max.45mm	Max.65mm	max.80mm	max.80mm	max.80mm
Packing speed	40-230bags/min	30-300bags/min	30-150bags/min	30-150bags/min	30-150bags/min
Power	220V 50/60HZ 2.4KW	220V 50/60HZ 2.8KW	220V 50/60HZ 2.8KW	220V 50/60HZ 2.8KW	220V 50/60HZ 2.8KW
Machine dimension	3920x670x1320	4020x720x1320	4020x820x1450	4020x920x1460	4020x980x1480
Machine weight	500kg	550kg	580kg	610kg	680kg