

YB-P8 Fully Automatic Spray Filling Rotary Rolling Capping Machine



Performance features:

1. PLC control system, color touch screen display.
2. The machine has the function of no bottle, no filling (only limited to peristaltic pump), no nozzle / no cover (if there is cover).
3. Stainless steel piston pump quantitative filling, pneumatic upper cover, lifting screw cover. It has the advantages of accurate filling measurement, stable capping and simple operation.
4. Double track bottle feeding, the upper cap positioning device can ensure that the nozzle plastic pipe can enter the bottle mouth accurately when it is too long or bent.
5. The filling needle is submerged into the bottom of the bottle to fill and slowly rise to prevent foaming. Grasp type flexible screw head, the tightness can be adjusted freely.
6. The main electrical components of the machine are of foreign famous brands.
7. The shell of the machine is made of 304 stainless steel, which meets GMP standard.

Technical parameters:

Model	YB-P8
Filing head number	8
Adding pump head	2
Capping head number	2
Filling volume	20-200ml (can be customized)
Capacity	80-100 bottles/min
Filling accuracy	≤ ±1%
Pass rate	≥ 98%
Power supply	1 Ph. AC220V, 50/60Hz
Total power	1.8 KW
Net weight	650kg
Overall dimension	L2400 × W1900 × H1500mm