

## **BD-18** Automatic Liquid Packaging Machine



BD-18 Automatic Liquid Packaging Machine. Microcomputer Packaging Machine. The process of measuring, bag-making, filling, sealing, printing and cutting can be done automatically. The packaging machine can pack many kinds of material such as grain, powder, liquid and tablet, etc. Packaging Material: Various Laminate Film, for example: Polypropylene / Polythene, Polyester / Aluminum foil / Polythene, Polyester / Aluminum-plating / Polythene, Nylon / Polythene, Polyester / Polythene. Purpose: Liquid and sauce kind: Syrup, honey, jam, ketchup, shampoo, liquid pesticide. Adopts CPU to control each function states, and setup the man-machine conversation interface. The Double channel temperature of the horizontal and vertical is controlled by intelligent temperature controlling device. Intelligent photo cell orientation, transform discretionarily between the light/shade. Strongly anti-jamming, when two bags can't catch up with the upper mark the machine will stop and give an alarm. The packaging speed can be adjusted continuously within specified range. Orientation open mouth and stop. The bag-making has high precision. Easily Operation and maintain. Measurement adopts adjustable cup method, which is accorded with the national measurement standard. Optional devices: The above machine may be changed into 4-side-sealing and equipped with hot stamp imprinting machine. It is choice to be stirring mechanism, hackle cutters, point line cutters, easy-tearing cutters and exhaust. It is choice to be both heat-sealing mechanism and net or even heat-sealing channel veins. Liquid packaging machine can choose antisepsis measuring mechanism (Aim at pesticide industry). The machine that has special bag-size or measuring requirement can be devised and produced specially.

## **Technical Parameters:**

Model	BD-18
Production Capacity	40-60 bag/min (depend on the material and specifications)
Pouch Length	50-120 mm
Pouch Width	60-85 mm
Seal Style	3 sides
Filling Volume	1-50 ml
Measuring Method	Piston Pump
Power	220V,50Hz,0.86Kw
Packing Size	800*700*1600 mm
Packing Weight	200 Kg