



WU-HSING ELECTRONICS CO., LTD.
since 1991

W-DC Series Floor type pneumatically



Wu-Hsing brand Pneumatic control Direct Heat Sealer comes with alum. Casting, Temperature control comes with a Thermostat (EGO) and upper & down sealing jaws is excellent for sealing heat-resistant materials: Nylon, KOP, Alum. Foil Cellophane, Kraft paper... Sealers are for having a beautiful mesh (++)or serrated(==) pattern sealing. Must warm up 10 minutes and keep its setting temperature.

2 hands hold the bags well operated to make an excellent and perfect sealing by pressing Foot Switch. (Caution: higher temperature.)

Max. temperature: 300°C (adjustable)

Sealing time: 0-6 sec.

Sealing width: 15mm or 10mm

Warm up time: 10 min.

Customer needs to prepare an air Compressor: 5-7kg/cm².

Optional device: Date Imprinter, Digital Temperature Controller, Air Unit, Emergency Stop Switch, bags Alignment plate, Front protective plates.

Applications: food, electronics, chemicals, pharmaceutical, and hardware components industries

Specification

Specification	W-220DC	W-250DC	W-300DC	W-450DC
Voltage	100V/110V/220V/240V			
Power (Watt.)	250W	300W	350W	450W
Max. sealing	220*15mm	250*15mm	300*15mm	450*15mm
Sealing Time	10 min.			
Max. Temp	300°C			
Dimension	34*34*90cm	34*34*90cm	34*34*90cm	48*34*90cm
Weight	18 KG	19 KG	21 KG	22 KG