

Auto Sleeving Machine **DSL-250A**



MACHINE FEATURES

- 1. Multiple communications interfaces for DeviceNet, ControlNET, EtherNet/IP, Profibus DP and analog for increase system compatibility.
- 2. No need to change the specially designed cutter plate within the rated specifications. Change of cutter plate in only three minutes.
- 3. Color touch panel control system ensures machine is operator friendly.
- 4. Forceful insertion designs can lower production costs.
- 5. Integrated adjustment design for the entire transmission mechanism gives you the maximum convenience for accommodating different types of label specifications.
- 6. Accommodates film paper core size of 5" to 10" with variable adjustments.
- 7. With unique programmed servo speed acceleration/deceleration curve, for reducing machine wear and tear to minimum level.
- 8. Instead of conventional control, we adapt network based advanced communication fuzzy servo control system to increase accuracy and speed.
- 9. No need to adjust label or bottle sensors when changing speeds.

Specification

Max speed	250BPM。
Bottle Diameters	φ25mm~φ125mm。
Film Material	PVC /PET /OPS。
Film Width	PVC: 0.035mm~0.08mm, PET: 0.04mm~0.06mm, OPS: 0.04mm~0.06mm 。
Machine Size	900mm*897mm*2452mm(L*W*H) 。
Voltage	3P;220V,380V,440V(Choose one from the given selection)。

PACKAGING TYPES



Cap
Sealing Type



Overall
Bottle Type



Full Body
Labeling Type



Fixed Middle Body
Labeling Type



Underlap
Labeling Type