

Quality System Registered ISO 9001:2015

Automatic Sleeving Machine



| Model | ASL-1000 | ASL-2000 |
|---------------------------|--------------------|----------|
| Dimension (mm) | 1720W*1060D*2500H | |
| Electric power | AC 3-Phases 220V | |
| Sleeving speed(bpm) | 100~250 | 250~500 |
| Diameter of bottle | Ø30-140mm | |
| Height of bottle | Max. 320mm | |
| Material of Shrink sleeve | PVC, PET, OPS, PLA | |
| Thickness of sleeve | 0.025-0.08mm | |
| Height of sleeve | Max. 250mm | |
| Diameter of sleeve's core | 3",5", 6", 10" | |

FEATURE

Easy Adjustment and Operation

Fully automatic model with HMI panel, easily settings change with buttons and advance input device.

Easy Maintenance

Simplified integration and consistent terminology for easier operation and maintenance. No lubrication required.

High-quality stainless steel and strengthful aluminum construction make it a durable specialty.

Various Production Range and Capacity

Available for various width ranging from 30mm to 140mm offering additional versatility for production.

A Variety of Applications

Tamper evident, overall-body, middle-body, and full-body sleeve.

rampor orraom, oronan so

 Performance Guarantee
Every Allen machine leaves our factory with robust performance quarantee.

