

# Shrink Packaging Machine



## Features

- Full re-circulating air chamber.
- PID temperature control.
- Adjustable air velocity control.
- Conveyor speed is adjustable.
- Roller conveyor. Teflon mesh overlay is optional.
- Automatic shut off after tunnel cool down.
- The electrical control parts has overheat compensator protection to shut off the power.

## ➤ CN-4520US/6530US Heat Shrink Tunnel



## ➤ CN-4520PD/6530PD Heat Shrink Tunnel

### Features

- Full re-circulating air chamber.
- Dual heat insulation plate unable causes around temperature overhrot. The safety shields-protect from heat.
- PID temperature control.
- Conveyor chain used the solid roller, exterior is packed by high temperature silica gel , burden with heavy products.
- Roller conveyor. Teflon mesh overlay is optional.
- The electrical control parts has overheat compensator protection to shut off the power.



## Specifications

Model	CN-4520US	CN-6530US	CN-4520PD	CN-6530PD
Power supply	3φ,220V/380V			
Watts	18 kw	24 kw	9 kw	15 kw
Tunnel size(LxWxH)	700 x 450 x 200 mm	1200 x 650 x 300 mm	1000 x 450 x 200 mm	1200 x 650 x 300 mm
Conveyor speed	2~10 M/min		10 M/min	
Conveyor size(LxWxH)	1000 x 450 x800 mm	1600 x 650 x 800 mm	1400 x 450 x 200 mm	1600 x 650 x 760 mm
Machine size(LxWxH)	1000 x 665 x1500 mm	1600 x 865 x 1600 mm	1400 x 760 x 1450 mm	1600 x 960 x 1550 mm

※ Customized specifications are available.



➤ CN-4520AL+CHL-4550A



➤ CN-4520AL+CHL-5050B



➤ CHM-8040A+CN-8540E



➤ CN-4520US+CHL-4050C

# Shrink Packaging Machine

## Features

- This machine is using infrared ray heater, all kinds of shrinkable films are available for our machines.
- The conveyer speed is controlled by precision electric stepless type instrument, speed is adjustable and highly stable.
- Adopting automatic temperature controller or constant temperature controller (according to customer need).
- The conveyor belt can be made in roll type, net type or teflon net according to the character of the products.



**CN-4015A/4520A/4520AL**  
Mini Shrink Tunnel



**CN-4520P/6530P/8540P**  
POF Shrink Tunnel

## Features

- There are two types of shrink tunnel-heat conduction type and heat circulating type.
- The conveyer can adopt the close-roller type or net type, suitable for big or small products.
- The conveyor speed and the tunnel temperature can be easily adjusted in order to accomplish the perfect shrinking effect.

**CN-4530E/6530E/8540E**  
PE Shrink Tunnel

## Features

- This machine adopts heat circulating type tunnel, temperature averagely spread. Special design and high safety.
- The cooling equipment is installed in the exit of machine to accomplish the perfect shrinking effect.
- There are two conveyor models to choice-roller type and net type, suitable for big and small products.
- Special design for PE film packaging.
- Auto temperature control can be adjusted for desired temperature.



## Specifications

Model	Unit	CN-4015A	CN-4520A	CN-4520AL	CN-4520P	CN-6530P	CN-8540P	CN-4530E	CN-6530E	CN-8540E
Power supply	-	1φ, 220V/240V			3φ, 220V/380V		3φ, 220V/380V/440V			
Watts	kw	5	6	9.6	12	15	18	24	36	
Tunnel size(LxWxH)	mm	700x400x150	800x450x200	1000x450x200	1000x450x200	1000x650x300	1200x850x400	1500x450x300	1800x650x300	2000x850x400
Conveyor speed	-	0~10 M/min				2~8 M/min				
Conveyor size(LxWxH)	mm	1050x400x690	1200x450x690	1500x450x760	1600x450x760	1600x650x760	2000x850x760	2400x450x760	3000x650x760	3000x850x760
Machine size(LxWxH)	mm	1180x620x1050	1330x720x1100	1650x720x1220	1600x730x1300	1600x930x1400	2000x1170x1500	2400x790x1300	3000x970x1400	3000x1170x1500

※ Customized specifications are available.

## CHUEN AN MACHINERY INDUSTRIAL CO., LTD.

PROFESSIONAL PACKAGING MACHINERY MANUFACTURER

No.16, Chiu Sir Lane, Chiu Sir Li, Pei Tun Dist, Taichung City, Taiwan R.O.C  
 TEL:886-4-2437 2958 • 886-4-2437 2075  
 E-mail:chuenan.chuenan@msa.hinet.net  
 chuenan@tcts.seed.net.tw

FAX:886-4-2437 1703  
 http://www.chuen-an.com  
 www.anpack.biz