

Automatic Multi Head ROPP Cap Sealing Machine LPTAMRCS-100/150/200



Salient features:

- No bottle no cap sensor.
- S.S. elegantly matt finished body.
- Adjustable height of conveyor belt, to align with other machine of the line.
- Sealing pressure can be varied to suit different gauges and size of caps.
- Low noise level, low power consumptions.
- Drain tray around the machine platform.
- VFD to synchronize, Conveyor, Star wheel and Platform turret & capping bowl.
- Universal coupling for quick and easy setting of In-feed worm.
- Adjustable bottle height gauge for easy and quick setting.
- In compliance with cGMP

Model	LPTAMRCS-100	LPTAMRCS-150	LPTAMRCS-200
Out put / Hour	60BPM to 80BPM	90BPM to 120BPM	120BPM to 160BPM
Direction of Movement	Left to Right		
No. of head	4 Nos.	6 Nos.	8 Nos.
Electric Specifications			
Main Motor	1.5 HP/415 Volts/50Hz		2HP/415 Volts/50Hz
Cap Feeding Bowl	0.25 HP/41Volts/50Hz		0.25HP/415Volts/50Hz
Change parts required	(A) Container: Star wheel, Centre guide, Feedwarm (B) Cap: Die, Delivery chute, bowl		