



## Dry Ink Coding Continuous Band Sealer (Vertical)

**FRM-1120L** is designed to quickly and efficiently seal any thermoplastic material including PE, PPE, stand up pouches, gusseted bags, and moisture barrier bags. This sealer can also be used in a wide array of fields such as: food, medical, and cosmetics industries.

### Features :~

- Durable stainless steel construction
- Easy to operate - minimal operator training
- Fast warm up time
- Ideal for medium duty applications
- Tilting seal head which allows the machine to tilt up to 30 degrees
- Suitable for any product including liquids
- Solid state digital temperature controller that maintains the seal bars at a proper temperature for consistent seal quality
- Motorized rubber conveyor for speed control
- Knurled pressure wheels with variable pressure adjustment
- Sealing method - constant/direct heat accompanied with a pair each of cooling and heating blocks
- Fully adjustable conveyor (both height and depth of conveyor in relation to seal bars can be adjusted)
- Dry ink coding allows for printing at the seal line
- Unit feeds from Right to Left
- Spare Parts Kit Includes: PC Board, PTFE Belt, Wheel Belt, Carbon Brush, and Typeset



### Specification :~

|                   |                     |
|-------------------|---------------------|
| Model             | FRM-1120L           |
| Power             | 110v / 60Hz         |
| Motor Power       | 50w                 |
| Sealing Speed     | 0-394 inches/minute |
| Temperature Range | 0-300°C             |
| Dimensions        | 43" x 24" x 41"     |
| Weight            | 187lbs / 275(Gw)    |

\* Designs and specifications are subject to change for improvement without prior notice.

## BAN HING HOLDING SDN BHD

No. 13-3, Jalan Raja Laut, 50350 Kuala Lumpur, Malaysia.

Tel: 603-4048 1000 / 4042 5970

Fax: 603-4050 8000

Website: [www.banhing.com](http://www.banhing.com)

Email: [enquiry@banhing.com](mailto:enquiry@banhing.com)