

HYL-B700

高速回转式贴标机 High Speed Rotary table Labeling Machine

Labeling Machine
Animal Drug QR Track & Trace System
Gs1 Serialisation Track & Trace System



产品描述

B700 适用于安瓿瓶、西林瓶、以及其他窄小圆瓶的高精度高速贴标，盘到盘立式输送及螺杆式分料特别适合于站立不稳的窄小瓶子的高速贴标要求。整机增加了标签三期打印及CCD相机检测，同时增加了漏贴标机检测和自动剔除功能。整机采用友好软件界面控制，确保整个生产信息全部有效记录，同时可以导出生产信息进行追溯查询，完美连接融入生产MES系统。

Product Description

B700 is specially designed for high speed and precision labeling on ampoules, vials, and other pharmaceutical bottles that cannot stand stably for transport..

性能及特点

- 立式瓶身三点定位贴标，避免普通立式贴标时瓶底不平及与瓶身垂直度误差造成的贴标歪斜，确保贴标精度。
- POM分料螺杆确保运转顺畅和持久耐用，不易碎瓶。
- CCD相机检测装置提供多种检测功能，如标签贴标检测、漏码检测以及打印内容检测等；不合格产品将被剔除回收。
- 整机采用WINDOWS友好软件操作界面，可以记录整个生产信息和导出生产报表。

Performance & Features

- tray-to-tray operation and spacing worm for convenient standalone operation. Rotary indexing table aligns bottles at three points enabling extra stability and high precision labeling at all speeds
- Unique mechanism effectively avoids bottle breakage thus allows smooth operation at very high speed.
- Optional label and code CCD Camera inspection .Patented positive drive rejection wheel mechanism ensures accurate rejection of defective products orderly during high speed operation.
- Whole machine adopts windows friendly software operation interface, Record all production information and export production report.

技术参数 / Technical parameters

类别	技术参数
贴标速度	Labeling speed 700 bottles/min
贴标精度	Labeling precision ±0.5mm
电源及功率	Power supply 220VAC 50/60HZ. 2.5kw
使用环境温度	Working temperature 0~50℃
气压	Air pressure 0.4~0.6MPa
外形尺寸(长X宽X高)	Dimension (long X width X height) 2500x1600x1200mm
总重量	Total weight 600KG