

Automatic Sachet Hand Sanitizer Shampoo/Sauce Packing Machine HY-QY50/HY-Y50



Suitable for automatic packaging of liquid paste products in cosmetics, food, health care, pharmaceutical industry, such as: cleanser, skin cream, mask mud, repair cream, essence milk, liquid, lotion, shampoo, conditioner, hair mask, fog eyebrow milk, etc.; chili sauce, soy sauce, mustard sauce, salad dressing, tomato sauce, etc.; enzyme drink, enzyme jelly, energy supplement, etc.; syrup, red ginseng drink, antibacterial cream, dampness Cream, acne cream, etc.

Features

1. Using a rotary cutter to cut, by replacing the blade, the flat mouth and the serrated mouth effect can be realized, and the bag length cutting position is convenient to adjust.
2. Full pneumatic control including metering and bag making, simple operation, less wear parts in the later period, reducing parts replacement.
3. Material: The material contact part is made of SUS304 stainless steel, which meets the requirements of GMP production.
4. The heat-generating parts and moving parts are hidden in the protective cover and are safe to operate.
5. The equipment is equipped with casters for easy handling and movement.

Characteristics:

1. The equipment is easy to operate and easy to maintain.
2. The whole bracket is made of all stainless steel, non-outsourced stainless steel.
3. The equipment is compatible, and different specifications can be realized by changing the mold.

4. Select a suitable metering pump body according to the material characteristics, and some materials can increase the fluidity of the constant temperature mixing tank to keep the material body.

5. Auxiliary equipment: loading machine + ribbon coding machine.

Specification:

Model	HY-QY50	HY-Y50
Filling Range	1-50ml	1-50ml
Sachet Size	W: 30-100mm, L: 30-150mm	W: 30-100mm, L: 30-150mm
Max. Film width	220mm	220mm
Sachet Type	3 sides/4 sides	3 sides/4 sides
Filling Method	Piston pump/magnetic pump	Piston pump/magnetic pump
Control	SIEMENS PLC + TOUCH SCREEN	EASY PACK CONTROL
Capacity	30-50ppm	30-50ppm
Power	220V50-60HZ/1.0KW	220V50-60HZ/1.0KW
Air	0.3m ³ /min 0.6-0.8Mpa	0.3m ³ /min 0.6-0.8Mpa
Materials	Case and contacting parts SUS304	Case SUS202; Contacting parts SUS304
Dimension (L*W*H)	880*700*1750mm	670*850*1655mm
Weight	250KG	200KG