



Labeling Machines AAM-510



This Wrap Around Labeling Machine is designed for wrap-around labeling on cylindrical bottles and containers. It can be incorporated with a line or operated individually.

Features:

- Machine meets current GMP standards.
- Japan PLC combine with Proface human / machine inter face LCD touch screen control.
- Japan precision 5-phase stepping motor and driver.
- Stainless steel frame construction is standard.
- Labeling speed is automatically synchronized with conveyor speed to ensure quality labeling.
- When the hot foil printer ribbon runs out, this labeler will stop and provide an "error" message.

Options:

- Hot Foil Printer for date-coding.
- Product feeding turn table (diameter 650/800/1000mm.)
- Product separating screw for high speed labeling.
- LRD-6110 Lion Sensor for transparent labels (USA made).

- "Push & Press" optional attachment is used to ensure smooth labeling without wrinkles or bubbles.
- Tapered products can take advantage of the "Labeling Heads Angle Adjustment" up to 15 degree for conforming to the product shape.
- Product separating screw for high speed labeling.
- LRD-6110 Lion Sensor for transparent labels (USA made).

Specification:

Model	AAM-510
Label Width	A Type/1-12 cm, C Type/1-18 cm
	D type:1-22 cm, E type:1-25 cm
Label Length	1.5~30 cm
Product Thickness (diameter)	2.5-10 cm (bigger size is available on request)
Reel Diameter (Inner/Outer)	7.6~36cm (Max.)
Labeling Speed	12-38 Meter, 12-70 Meter (Servo motor) per minute
Power Consumption	750W