
SFA-2125-L / SFA-2124-L & SFA-2125-L (PULL TYPE)





SFA-2125-L (PULL TYPE)

Association of course under the course of th

- Human-Computer Interaction Design.
- Fully Wrap Around carton packing and Tray Packing operation.
- The large processing range comprises PVC, PE, PET, PP Bottles, Glass Bottles, Cans and aluminum cans etc.
- Parameters can be set and modified on the screen.
- Glue Spraying distance is control by encoder, ensuring consistent glue spraying length on each carton and permit adjustment and memorizing at any time.
- Minimization of the changeover times, in order to quickly Switch from a production to another one
- All movable parts are provided with grease nozzle for lubrication. Hard-toreach bearings located at the machine bottom are centralized lubrication at outside through oil tubes.
- CE Certification.

SPECIFICATIONS

MUDEL	214-2129-F	SFA-2124-L	SFA-Z1Z5-L (PULLT)
POWER SOURCE	According to Installation Place, Local Electricity Sources		
POWER CAPACITY	8 KW		
AIR PRESSURE	5.0~7.0 kg/cm²		
MACHINE DIMENSIONS	L : 6070 x W : 2800 x H : 2006 mm		
MACHINE WEIGHT	1500 kg		
PROCESSING CAPACITY	25 case/min	25 case/min	13 case/min
OPERATION CONTROL	English / Chinese Display System		
SUITABLE PROCESSING PACKAGE			Mold Free Application