



Spout-mounting, Air-sucking & Sealing Machine SY-M903VT



PRODUCT DESCRIPTION:

MODEL: SY-M903VT

1. Applications: For any premade heat sealable pouch.
2. Distance from content to be packed to the bag opening should be over 50mm at least.
3. Sealing head can be tilted 0~15° degree forward.
4. The bag is sealed with air extracted to reduce the volume of bag.
5. Air extracting device.
6. Control panel is equipped with touch screen.

Optional devices:

- Stainless steel (SUS#304)
- Coder (solid ink or hot foil)

Specifications:

Power	1800W
Packing speed	0~10 m/minute (adjustable)
Power supply	AC200V/220V/240V, single phase 50/60HZ
Conveying direction	From left to right
Conveyor width	200mm
Bag size	Within 300mm Long 300mm Wide
Temperature range	50°C~300°C
Heating power	600W×2pcs
Conveyor height adjustable range	90mm
Conveyor load weight	5 Kg
Sealing width	5mm (applicable to PE, PP) or10mm , either one
Packing material thickness	0.06-0.5mm (double-layer thickness)
Machine size	1560L 720W 1010H (mm)
Packing size	1660L 820W 1110H (mm)
Packing function	Sealing + air extracting
Remark	For the standard specifications described above, we reserve the right to change without prior notice.