



High Speed Side Sealing & Shrinking FL-5545TBH+SM-5030LX



Features:

- FL-5545TBH High speed side sealer detects product automatic with photocells, optional feed type automatically and manually, available with centre fold film to seal other three sides accomplish fully automatic shrink wrapping
- FL-5545TBH High speed side sealer detects product automatic with photocells, optional feed type automatically and manually, available with centre fold film to seal other three sides accomplish fully automatic shrink wrapping
- Continuous side seal without product length limit
- Able to increase logo locate function for printed film
- Servo motor control cross seal system ensures accurate position and perfect seal line, double pulling poles make seal blade stable for long time operation. Constant temperature seal system use POF and other industry shrink film
- Adjustable speed feeding system and free rolls storage table realize truly high speed and unmanned operation; optional products distribute system for different products
- SM-5030LX high speed hot wind shrink tunnel adopts roll conveyor belt covered hot proof silicone tube, each roller can be rotated, visible window shows shrink process in tunnel
- Uniform temperature tunnel use PVC, POF and other different shrink film
- Inner insulate shell results into circle hot wind, adjust convey speed to reach best shrink effect for different packaging request
- Equipped fingers pushing conveyor or belt conveyor controls equal distance among products to reach higher packing speed and better shrink effect

Scope:

- This series of models using hot air circulation shrink, mainly shrink label for bottle-shaped bottle, jars, cups etc.
- For food, beverages, pharmaceuticals, cosmetics, pesticides and other industries glass bottles, plastic bottles, cups and other containers, bottle or cup body heat shrinkable sleeve label after label

Specifications:

Model	FL-5545TBH	FL-5560TBH	FL-5580TBH
Machine dimension L×W×H(mm)	2040×1480×1300	2260×1600×1300	2350×1760×1320
Max packing size L(mm) H<150	Unlimited	Unlimited	Unlimited
Max packing size W+H(mm)	≤400	≤600	≤700
Cross sealing L(mm)	450	600	800
Packing speed (pcs/min)	40-60	40-60	40-60
Net weight (kg)	800	900	1000
Power (kw)	3	3.2	3.4
Power supply	1PH 110V/220V 50/60Hz	1PH 110V/220V 50/60Hz	1PH 110V/220V 50/60Hz
Air pressure (kg/cm ²)	6-8	6-8	6-8
Applicable film	POF	POF	POF

Model	SM-5030LX	SM-6530LX	SM-8030LX
Machine dimension L×W×H(mm)	1800×990×1300	1800×1140×1300	1800×1290×1300
Tunnel dimension L×W×H(mm)	1500×600×300	1500×650×300	1500×800×300
Max packing size L(mm) H<150	1300×400×250	1300×550×250	1300×700×250
Conveyor speed (m/min)	0-20M	0-20M	0-20M
Net weight (kg)	650	700	750
Power (kw)	16	18	20
Power supply	3PH 220V/380V 50/60Hz	3PH 220V/380V 50/60Hz	3PH 220V/380V 50/60Hz
Applicable film	POF	POF	POF

