

Heat Shrinkable Horizontal Flow Wrap Packing Machine ZW-590



Food, beverage group packaging, bowl noodles, milk tea, mosquito coils, wallpaper, exercise books, filters, electrical switches, various tools, industrial parts and daily cosmetics body packaging.

Performance characteristics:

- Suitable for bulk packaging of single product or multiple product
- Three servo control, the bag length is set and cut, no need to adjust empty walk, one step in place, save time and film
- Color touch screen control, parameter setting is convenient and fast, it can dozens of packaging parameters
- Fault self-diagnosis function, fault display at a glance
- High sensitivity photoelectric eye color mark tracking, mathematically input the sealing position, so that the sealing position is more accurate
- Temperature independent PID control, better suitable for all kinds of coating materials
- Location stop function, no sticking knife, no waste film
- The transmission system is simple, reliable and easy to maintain
- Cut to the product automatic inversion, restart directly after boot convenient operation
- Adding anti-cutting device, the machine will stop automatically when the product is misaligned
- Suitable for matching with automatic marking machine
- Adding waste recycling device makes packaging more beautiful and save about 20%-30% material than traditional folding film packaging machine

Technical Parameter:

Model	120	150	180	210
max film size	less than 590mm	less than 590mm	less than 590mm	less than 590mm
packing size	L	60-320mm	150-530mm	180-600mm
	W	10-200mm	10-200mm	10-200mm
	H	5-35mm	75-100mm	80-130mm
packing speed	30-150 bags/min	30-150 bags/min	30-150 bags/min	30-150 bag/min
film type	PVC,POF etc	PVC,POF etc	PVC,POF etc	PVC,POF etc
power consumption	3.6KW+16.5KW	3.6KW+16.5KW	3.6KW+16.5KW	3.6KW+16.5KW
power supply	220V/50HZ+380V/50HZ	220V/50HZ+380V/50HZ	220V/50HZ+380V/50HZ	220V/50HZ+380V/50HZ
envelop dimensions	5000*1170*1500mm	5000*1170*1500mm	5000*1170*1500mm	5000*1170*1500mm
shrink machine	2400*600*1700mm	2400*600*1700mm	2400*600*1700mm	2400*600*1700mm
weight	1000kgs+600kgs	1000kgs+600kgs	1000kgs+600kgs	1000kgs+600kgs