

Horizontal Continuous Flow Wrapper Pillow Bag Bars Packing Machine



Suitable for bread, moon cake, cake, paper box and tray and solid material package.

Main feature:

1. Stainless steel machine body, elegant appearance and durable

2. The bag length without human setting, can be automatically detected during machine operation and set automatically

3. Simple machine structure of servo motor, easy maintain, less wear and long lifetime

4. The main control circuit adopt single machine control, display on the touch screen, servo motor control, superior human interface, easy operation, and clear at a glance

5. Packing speed and the length of forming bag can be controlled by servo motor, stepless speed, widen the adjustment range, can well match to the front part processing line

6. High sensitivity photocell tracked accurately automatically

7. Sealing temperature independent control, suitable for many packing material, firm and elegant sealing

8. Can equip with Intermittent Pneumatic Devices and spraying alcohol device

Main technical parameter:

| De el la en en el el | |
|----------------------|---|
| Packing speed | 30-200 bags/min |
| Bag length | L :130-400MM W:50-160MM H:3-70MM |
| Film width | 80-350mm |
| Packing material | OPP/CPP, PT/TE, KOP/CPP, ALU-FOL |
| Outer size | L 4000*W 950 *H1600MM |
| Heating power | 3.5kw |
| Power | 0.55+0.75kw |
| Total power | 4.8kw |
| Machine weight | 630kg |
| Optical device | ribbon printer, flushing device, bread falling feeder, stacking machine, guide bar, hair removing and gusset device |