



Link-50B High Quality Automatic Carton Forming And Sealer Carton Sealing Machine



SCF-50B upper and lower drive carton sealing machine, upper and lower belt drive, using sticky tape sealing, upper and lower sealing, fast and stable, and the sealing effect is smooth, standardized and beautiful, the width and height can be adjusted manually according to the carton specifications, simple, Fast and convenient, it can replace labor, improve production efficiency by up to 80%, and save 5-10% of consumables. It is a good choice for enterprises to save costs, improve production efficiency, and realize packaging standardization. The upper and lower drive carton sealing machine is also called the upper and lower drive tape sealing machine. It is manually adjusted according to the size of the carton. If it is necessary to automatically identify and adjust the size of the carton, it is recommended to use a fully automatic carton sealing machine (automatic adjustment).

Features of carton sealing machine:

- .Manufactured with international advanced technology, and selected imported parts and electrical components;
- The standard machine table height is 600mm;
- . Manually adjust the width and height according to the carton specifications;
- The transmission mode adopts upper and lower belt drive;
- Suitable for taller and heavy duty cartons;
- Equipped with blade guard. Avoid accidental stabbing during operation;
- Manually fold the upper cover, and seal the box with the upper and lower characters at one time;
- It can be operated on a stand-alone machine, or it can be used in conjunction with an automated packaging line. It is the choice for enterprises to save costs, improve production efficiency, and achieve packaging standardization.

Application range of sealing machine:

Relying on the above advantages, the upper and lower drive case sealing machines are widely used in food, medicine, beverages, tobacco, daily chemicals, hardware, toys, electronics and other industries at home and abroad.

Technical Parameters:

Model	Link-50B
Applicable to the power supply	220V/50Hz / 0.2KW
Minimum packing size	L 150 * W 180 * H 130mm
Maximum packing size	L Unlimited * W 500 * H 500mm
Mesa height	H 600mm-650mm
The belt speed	20 m/min
Packing tape	BOPP/PVC
Tape size	W48, 58, 72mm
Installation dimensions	L 1000 * W 900 * 1330mm
The net weight	160Kg