

DXSL-40II / 150II Sticky-liquid Packaging Machine



It is suitable for automatically packaging of viscous products with free-flowing such as tomato sauce lotion noodle jam, edible oil, meat jam and broth. The processes of bag making measuring, filling, sealing, counting and hot pressing codes can be done automatically. Packing material include several kinds of heat-seal lamination, such as PET/plated AL/PE, PET/PE, NYLON ...etc.

Features:

- All stainless steel cover meets to GMP standard.
- The machine is suitable for hot sealing and assembling attemperator depend on customers requirement.
- Automatic adjustment of pouch size and filling range.
- Automatic self support lubricating system, the machine can work 24 hours and the maximal opacity is 100 begs/min.
- The operation facility is controlled by American intel computer, all function is displayed with digital screen.
- Minimum sealing temperature variation employs PID temperature, the tolerance is controlled by $\pm 2\%$.
- The machine can be equipped with a product stirrer and heated jacket for high temperature product packaging.
- Ink printer and conveyor are as an option.

Technical Parameter:

Model	DXSL-40II	DXSL-150II
Bag size (mm)	(L) 55-110 (W) 20-80	(L) 70-150 (W) 70-115
Capacity (bags/min)	30-100	28-80
Max. filling range (ml)	40	150
Dimension (mm³)	600 x 790 x 1780	700 x 800 x 1900
Weight (kg)	320	340
Power	220V,50Hz,1.5kW	220V,50Hz,1.9kW