

## *Glass Bottle Ampoule Washing Sterilization Filling Sealing Production Line*



The linkage line consists of vertical ultrasonic washing machine, hot air circulation sterilization tunnel, filling and sealing machine. It can be used in combination or in single machine. The linkage line can complete water spray filling, ultrasonic cleaning and flushing (internal and external), CA flushing (internal and external), preheating, drying and sterilization to remove heat source, cooling, before and after nitrogen, filling, sealing after preheating, sealing and other processes. This line can meet the size range from 1-20ml ampoule of washing, drying and sterilizing to remove heat source, filling and sealing requirements of the production process.

### **Technical Parameter**

Product Model	HABL-6	HABL-8	HABL-10	HABL-12	HABL-16
Suitable size(ml)	1-20ML	1-20ML	1-20ML	1-20ML	1-10ML
Output (pcs/h)	6000-16000	8000-21000	10000-24000	12000-30000	16000-36000
Filling heads	6	8	10	12	16
Power supply	380V 50Hz	380V 50Hz	380V 50Hz	380V 50Hz	380V 50Hz
Power capacity (kw)	78	78	80	90	90
Total weight (kg)	8900	8900	9400	9700	10100
Overall dimensions(mm)	9100x2200 x2450	9100x2200 x2450	9260x2200 x2450	9910x2200 x2450	10042x2200 x2450