



SHENZHEN PENGLAI
SINCE 2003

YX-06-1000 *Fully automatic powder filling sealing machine*



YX-06-1000 Fully automatic powder filling sealing machine characteristics:

- Easy to operate, adopt advanced PLC from Germany Siemens, mate with touch screen and electric control system, the man-machine interface is friendly.
- Frequency conversion adjusts the speed: this machine uses frequency conversion equipment, can be adjusted within the range according to the needs of reality in production.
- Automatic checking: no pouch or pouch open error, no fill, no seal. the bag can be used again, avoid wasting packing materials and raw materials.
- Safety device: Machine stop at abnormal air pressure, heater disconnection alarm.
- Horizontal conveyer style to giving bag: it can put on more bags on the bag storage and have a low requirement about the quality of bags.
- Use the plastic bearing, don't need put on oil, less pollution.
- Use no oil vacuum pump, avoid polluting the environment in the production.
- The packing bag suits in extensive range, suit for multi-layer compound, monolayer PE , PP and so on Preformed bag made by film and paper.

YX-06-1000	
Working position	Six position
Material of bag	Laminated film, PE,PP ,ETC
Bag type	Stand-up bag, flat bag, zipper bag
Bag size	W 100-210mm L 100-410mm
Filling range	10-1000g
Weighing accuracy	±0.5-2g
Capacity	10-60bags/min
Voltage	380V 3phase 50HZ
Power	5.5KW
Air consumption	0.6m3/min(supply by user)
Overall Dimensions	4200*1800*2400mm weight 1280kg