

S-5647-IV-BX Flow Wrap Machine - Top Sealing - Box Motion



Great packaging solution for soft items, vegetables, and fruits, etc., the wrapper produces finished packages with less air and achieves optimal hermetic sealing. Flow pack machine for frozen cakes, ice pops, cheese, etc.

Features

- Powder coating machine frame construction.
- 3 axis servo motor drive for in-feed, fin sealing and end sealing.
- Yaskawa motion controller.
- 10.4" colorful touch panel (HMI).
- 100 sets of product data memories.
- Shinko P.I.D. temperature control modular.
- One set of box motion end sealing jaw.
- One set of auto centering reel holder.
- Two sets of inverted center sealing wheel, one cold & one heated.
- Japanese Panasonic photocell for film registration.
- Transfer belt under center sealing station.
- 2 M long top chain in-feed conveyor with adjustable guides.
- Safety protection guards for end sealing station.
- End sealer over-load protection device.
- European CE safety standards.

Specification

Model No.	S-5635-IV-BX	S-5647-IV-BX	S-5661-IV-BX
Capacity (PPM)	20 ~ 90	20 ~ 90	20 ~ 90
Bag Length (mm)	70 ~ 350	70 ~ 350	130 ~ 500
Max. Film Width (mm)	350	470	610
Max. Product Width (mm)	145	190	265
Max. Product Height (mm)	30 / 60 / 90 mm with jaws Dia. in 88 / 120 / 160 mm		
Electricity	4.1 KW - AC 220 Volt - 3 phase + Ground		