

CB-680XWS Flow Packing Machines



Description

- 5 independent motors (Conveyor, cutter, plastic film moving, movement of center sealing part, movement of end sealing part)
- Motion controller for quick response to various commands
- Accurate positioning
- Independent temperature control for center sealing and end sealing
- Food grade SS304 contact parts

Outstanding Features

- All control in one movable control panel, user-friendly and easy operation
- Box-motion cutter for high products packing and ensure the compact package
- Empty bag prevention, no product no bag
- Product cutting prevention, machine will stop once cutter cuts the product
- Memory function, can store 99 groups of package parameters (product position, packing speed, bag length)
- Independent control for movement of center sealing part and end sealing part, to meet different product height
- Have alternative choose for flexible length system no pusher and fix length with guide pusher
- Pure PE film can be use on the machine

Specification

Model	CB-680XWS
Film width	≤680mm
Film thickness	30-80um
Dimension of film bobbin	Outer diameter≤300mm Inner diameter≥75mm
Single knife bag size	L(60-6000)xW(25-320)xH(10-120)mm
Single knife packing speed	10-40bags/min
Power	220V,50HZ,5.2KW
Outer dimension	L5000xW1200xH1650mm
Machine weight	1080KG
Motor configuration	Full servo
Film bobbin position	Down
Blade cut type	Box motion / Reciprocating