

DPP-260H Automatic Al-Plastic Blister Packing Machine



DPP-260H Automatic Al-Plastic Blister packing Machine is our advanced equipment designed under updated improvement. It adopts the integral technology applying frequency inverter for speed control and mechanism, electricity, light and air to machine. Its design is in strict compliance with GMP standard and takes lead in the blister packer's filed. Featuring advanced functions, ease in operation, high output, the machine is the most ideal packing equipment for large and medium size pharmaceutical enterprises, health food and food stuff trades.

Features:

1. Adopts top brand PLC controller with touch screen displayed in Chinese and English, Frequency inverter for speed control, servo traction, which can ensure the length of blister traction adjustable within the range.
2. With thermal temperature control and test, main machine over loading protect, PVC and PTP packing material position test, feeder material position test, failure automatic debug and alarm, automatic protection and stop running.
3. The machine station module type design of level frame, good sight, safe and convenient operation.
4. Thermal with contact type, positive press formed, air cushion thermal seal upper and lower net, photo register make your product package better.
5. PVC exchange support with bigger type material support, whole roller, which makes the equipment more practicability.
6. The special design of moulds in rectangle shape, ladder type fixing, provide much convenience and ease to moulds replacement. All material contact parts adopt high quality stainless steel and aluminum metal, slap-up surface treatment craft.
7. Discharging finished product in right order, automatic collection of bad products, auto rewinding of strap material to ensure easy collection.
8. Feeding efficiently, reliable and suitable for many kinds type arrange and irregular feeding, (according to actual product design fit feeder).

9. The machine has been designed into separated body, which is easily move into lifts or workshops.

Technical Parameter:

MODEL	DPP-260H
Punching frequency	AL/Plastic 20-60times/min Al/AL 15-30times/min
Max production capacity	AL/Plastic 140 thous and Grains/hour Al/Al 75 thous and Grains/hour
Max forming depth	AL/Plastic 22mm Al/al 18mm (made to order)
Adjustable scope of Travel	made to order 30-140mm
Clean compressed air	Press 0.6-0.8Mpa
Air consumer (air compressor)	≥0.25m ³ /min(self prepared)
Power	380V 50HZ 8.5Kw
Dimension	4500x760x1620cm (can be separated)
Weight	1800kg