

## GPL-5545DH+GPS-5030LW Auto High-Speed Vertical L-Bar Sealer and Shrinking Packaging Machine



The auto side sealing shrink packaging machine is a high-speed vertical up and down sealing and shrinking packaging machine designed for the refined production of cosmetic films. Mainly for high and thin products, it can automatically complete the steps of feeding, film wrapping, sealing and cutting, shrinking, etc., to ensure that the sealing line is in the middle position, automatic film blowing, and the sealing line is thin, suitable for POF film and cross-linked film. The heat shrinkable packaging effect is beautiful, smooth and wrinkle-free, without personnel operation, the packaging speed is 5-80 Pcs/min, and the work efficiency is high. This sealing and shrinking packaging machine are also suitable for printing, color box, medicine, daily chemical, auto parts, food and other industries.

### FEATURES

- Vertical Drive Function: The sealing and cutting knife holder is controlled by vertical drive, which can overcome the problems of wrinkles and the sealing line not in the middle of the product caused by the traditional L-shaped sealing machine;
- Smart Touch Screen: Using the touch screen control panel, easy for the operator to input data and adjust, easy to use;
- Mitsubishi Servo Motor: To ensure the stable and smooth operation of the machine;
- Highly Automation: Automatically complete the steps of feeding, film wrapping, sealing and cutting, shrinking, etc., with high automatic program control;
- Safe and convenient: The machine panel is simple and easy to operate, and the whole machine is equipped with safety anti-cutting protection and alarm functions, which greatly protects the safety of the operator;

- **Packaging Effect:** The sealing line is thin and firm, and the heat shrinkable packaging effect is beautiful, smooth, and wrinkle-free, ensuring that the product is not damaged during storage and transportation.

## SPECIFICATIONS

MODEL	GPL-5545DH	GPS-5030LW
<b>Film</b>	POF	POF
<b>Packing speed</b>	20-60pcs/min	20-60pcs/min
<b>Packing size</b>	W+H<380mm, L+H<450mm,H<180mm, L≥100mm	L≤500mm, W+H≤450mm, W≤350mm,H≤230mm
<b>Cutter size/Tunnel size</b>	Cross cutter: 450mm Vertical cutter: 555mm	L: 1500mm W: 500mm H: 300mm
<b>Max temperature</b>	240°C	200°C
<b>Electrical</b>	220V 50-60Hz 3 Phase	220V/380V 50-60Hz 3 Phase
<b>Power</b>	4.0KW	15.5KW
<b>Max current</b>	10A	25A
<b>Air compressing</b>	0.6~0.85MPa	/
<b>Table height</b>	850-900mm	850-900mm
<b>Machine Dimension</b>	L1785×W1420×H1340mm	L1850xW1095xH1325mm
<b>Machine Weight</b>	650kg	650kg