

SED-660-45GY-B Auto Rotary Tablet Press Machine



This series is a double tablet-release with high-pressure high-speed. It adopts the latest foreign structural design and adopts the advanced servo control mode without hand wheel, which is simple and fast, and realizes product standardization, modularization and serialization.

This machine have the advantages of high precision, high speed, high automation, etc., so it is an ideal equipment for mass production.

Fully compliant with GMP requirements, it can suppress double-layer tablet, ring tablet, round tablet, engraving tablet and special-shaped tablet, suitable for high efficiency and precision pressing in pharmaceutical, food, chemical and other industries.

Main Features

1. High quality stainless steel structure, in line with cGMP requirements
2. Servo control without hand wheel, higher automation program
3. The tableting chamber has no dead angle structure, easy to observe and clean
4. Special anti-seepage oil, dustproof device
5. Overall safe and reliable, tight sealing and dustproof design
6. Easy to disassemble structure to ensure equipment maintainability

Product Parameters

Type	SED-660-45GY-B
Data	
No of station	26
Dimension	820×1100×1750mm
Net weight	1600 Kg
Main pressure	100KN
pre-pressure	16KN
Max filling depth	20mm
Diameter of die	38.1mm
Max tablet diameter	25mm
Diameter of punch	25.35mm
Pitch circle dia.	370mm
precision	±3%
Working noise	≤70dB
Main motor Power	7.5KW