

One Piece Carton Filler



The machine adopt to servo location, PLC controlling, auto operation, main drive adopt to import motor drive, multi degree rotation via chain, chain wheel speed regulator ect. It auto degree is high, reliable controlling, easy to adjust, intelligentize manipulation ect advantage, can widely used for beverage, beer, chemistry, food, medicine ect industry, can do all kind of tin and bottle second time package, can match with auto filling production line.

Main parameter

- Product capacity: 25carton per minute
- Rating power: 10KW
- Used power supply: three phase, 380V, 50Hz
- Controlling power supply: 24V DV
- Compressor air: 1500L per minute, 0.6-0.8Mpa
- Hot melting glue solidify time: 1.5-2S
- Machine weight: 3500kg
- Overall size: L6285*W2582*H2115MM
- Bottle entry conveyor size: L3000*W620*1200MM
- Package product overall size: Length 350-450,Width 230-330mm, Hieght: 85-320mm;

Applied bottle type:

Package product	Specification	Capacity	Applied bottle type
200ML-400ML	4*6,4*5,3*4or 3*5,2*3 ect	8-30carton/minute	PET/Tin/Glass bottle
300ML-500ML	4*6,4*5,3*4 or 3*5,2*3 ect	8-30 carton/minute	PET/Tin/Glass bottle
300ML-600ML	4*6,4*5,3*4 or 3*5,2*3 ect	8-30 carton/minute	PET/Tin/Glass bottle
500ML-1250ML	3*4,2*3 ect	8-30 carton/minute	PET/Tin/Glass bottle
1250ML-2500ML	2*3,2*2 ect	8-30 carton/minute	PET/Tin/Glass bottle