

## Gear Pump Liquid Filling Machine



This gear pump liquid filling machine is equipped with gear pump, which can fill you up with liquid to be precise. There are multiple nozzles there, and the customer can control each nozzle separately if needed. This fully automatic liquid filling machine is equipped with a conveying device and can be queued as part of the production. All these will help you greatly improve your work efficiency.

## Description

Rito machinery company's gear pump liquid filling machine is equipped with gear pump, which can fill you up with liquid to be precise. There are multiple nozzles there, and the customer can control each nozzle separately if needed. This fully automatic liquid filling machine is equipped with a conveying device and can be queued as part of the production. All these will help you greatly improve your work efficiency

## Feature:

1. Touch screen operation interface;

2. The anti-drip slot helps to clean the machine and ensures that the machine is clean and working better. Bottle separation plate can accurately separate bottles and prevent bottle leakage and waste

- 3. The pouring precision can reach + / 1%;
- 4. Grounding cylinder, unique grounding valve design, no leakage;
- 5. No bottle function, no flash, automatic bottle stop;
- 6. Develop different positioning devices according to the actual situation of the bottle;
- 7. The cleaning equipment is convenient and can be disassembled without tools. It can also be cleaned online or hot sterilization
- 8. PLC programmable Mitsubishi monitoring, Japan;

9. Frequency converter using Schneider, France;

10. The pneumatic components adopt Taiwan Airtac;

11. This part can be used to adjust the sensitivity of the electric eye to ensure that the machine works accurately

12. The equipment meets the health and safety standards. The user can choose the glass cover. 13. Filling Nozzles with anti-dripping function, can control each nozzle separately. We also have

the 2/6/8 nozzles filling machine, please send us message if you need it.

## **Technical Parameters:**

| Container size                   | φ20-160mm H30-300mm                      |                       |                       |                       |
|----------------------------------|--|-----------------------|-----------------------|-----------------------|
| Max flow rate                    | 5500ml/min                               | 5500ml/min            | 7500ml/min            | 12000ml/min           |
| Material of pump                 | 304stainless<br>steel                    | 316stainless<br>steel | 316stainless<br>steel | 304stainless<br>steel |
|                                  | ≤100ml deviation≤±1ml                    |                       |                       |                       |
| Filling accuracy                 | > 100ml deviation≤±1%                    |                       |                       |                       |
|                                  | ( based on water)                        |                       |                       |                       |
| Filling speed                    | 20-50pcs/min                             | 20-50pcs/min          | 25-60pcs/min          | 40-65pcs/min          |
|                                  | (depending on bottles and filing liquid) |                       |                       |                       |
| Power supply                     | 220V-50HZ/110V-60HZ                      |                       |                       |                       |
| The whole machine power          | 2000W                                    |                       |                       |                       |
| Packing weight                   | About 150kg                              |                       |                       |                       |
| Packing size                     | About 2000*820*1580mm                    |                       |                       |                       |
| Size of air compressor connector | OD8mm                                    |                       |                       |                       |