



## *KCTB-S Double Side/Single Side Automatic Labeling Machine*



This machine is applied to label the self-adhesive label on various cylindrical bottles, flat bottles, Square bottles. Suitable for double side and single side labeling.

This machine is widely used in pharmaceutical, foodstuff, beverage, cosmetic and chemical etc Industries.

### **Features**

- PLC control, touch screen operation interface, Simple and reliable.
- Open frame design, easy to adjust and change the label.
- Adjust speed through the transducer, anchor point is accurate.
- Outside and main parts are made of stainless steel, no pollution, easily cleaning, meet the GMP standard.
- Label count down (for precise run of set number of labels) to automatic shut off.
- The code printer is optional; the letter is clearly and firmed.
- Touch screen control system with job memory.
- Full-set protecting device keep operation steady and reliable.
- Adopts AUTONICS photoelectric system, the accuracy of identify label is very high. Stable and reliable.
- The noise of single machine is less than 50 dB

## Technical Parameters

Bottle size	Diameter: 30-100 mm height:60-350 mm
The range of applied label	Length: 0-150 mm height:10-200 mm
Power supply	AC,220V/50-60HZ
Power	800W
Labeling speed	0-100 bottle/min
The Max. outer diameter of reel	300 mm
The inside diameter of reel	76 mm
The labeling accuracy	+/- 1.0 mm
Working direction	Left à right
Weight	450 kg
Overall size	2400x1100x1450 mm