

JY-400E Automatic Flow Wrapping Machine



Main performance & characteristics

- 1. Adopt a higher precision Servo system, with PLC & AC inverter intelligent and step-less controlling which can realize simple operation and more correctly cutting.
- 2. High-sensitive photo sensor, automatically adjust, track, find cutting point, accumulatively count packs, Automatic measure bag length.
- 3. Digital and independent PID temperature controlling, suitable for various packing materials. New type double fin sealing design makes the packaging high efficiency and beauty.
- 4. Adjustable bag former and pitches enable the change of packing products conveniently.
- 5. The machine covered with full stainless steel materials. With timing belt transmission, Compact structure, lower noise and less shake.
- 6. Variety of optional device is available, Like: Touch screen/Date coder/Labels applicator/Euro slot or hole punch/Gusset forming /Nitrogen or gas inflation/Spraying alcohol/Automatic film splicer/ Auto feeding/Desiccant feeder /Auto falling/Products conveyor/No products no packing I Check weather / Metal detector etc.

Using range

Mainly used for various kinds of solid objects with regular shape (Square/Rectangle/Circular/Ellipse/Flake etc.), such as ice lolly, ice cream cone, cookies, bread, adhesive tape, pharmaceuticals tools, daily necessities, hardware, or any other products loaded in box or tray.

Technical parameter

Model	JY-400E
Packing speed (bag/minute)	30-200 bag/min
Packing size (mm)	L80-350
Length x Width x Height	W10-60/60-120
	H5-30/30-60
Maximum width of film (mm)	<400mm
Thickness of film (mm)	0.02mm
Power	220V,50/60HZ,2.8KW
Overall size (mm)	4400*940*1640mm
Weight	650kg
Package	2.6CBM,2CASES
Packing material	OPP/PP、OPP/CPP、PT/PE、PE、KOP/CPP、PT/PE/、AL/PE etc. Any heat-sealable composite materials foil/film