

Large Pouch Automatic Sauce Packing Machine XY-90BJ



This automatic sauce packing machine can be equipped with different weight and filling system for various liquid sauce packaging such as fresh milk, honey, oil, ketchup, paste, alcohol, soy sauce, vinegar etc.

Applicable Pouches: Pillow / back sealing /flat pouch, 3/4 side sealing pouch, stick/triangle pouch, gusseted/quatro pouch, doypack.

Features:

1. Imported PLC computer control system, color touch screen, easy operation and much more stable;
2. Separate pneumatic control and power control with low noise and more stable circuit;
3. Imported servo pulling film system and imported color sensor, accurate positioning, perfect operation;
4. Multiple automatic alarm protection, reducing the loss furthest;
5. Double belt pulling film to make the packaging bag smooth and perfect;
6. Enclosed mechanism is used to prevent dust entering effectively.

Main Function:

1. Reduce production cost and management cost. One packing lime reduces 4-10 workers, input cost will be in return within 1-2 years.
2. Upgrade products quality: the appearance and packing quality can meet unified standard.
3. Reduce defective rate, finished products ratio can reach to more than 99.5%, this can avoid the waste of manual packing.
4. Improve Hygienic standard: No direct contacting with persons, avoid man-made pollution.

Technical data:

Model	XY-90BJ
Sealing form	Bag Sealing
Measuring Scope	30g~1000 g/bag (special one can be customized)
Bag Size	L: 50~320mm W:30~200mm
Input Voltage	220V/50HZ 1 phase
Power	3.5 kw
Machine Weight	600KG
Machine Size	1400x2400x1800(L x W x H mm)
Packing material	Composite material such as POPP/PPP, POPP/VMCPP, PPP/PE etc. For example, the packing material is composed of glass paper, paper, polyester film, aluminum foil and with compound high pressure polyethylene coated inside. Outer circle should be flat, OD is less than or equal to 360mm, skeleton ID is equal to 75mm, film width is less than or equal to 420mm.
Work Condition	Temperature: -5 degree centigrade to 45 degree centigrade, no freezing.
	Relative Humidity: 30-85%, no dewing.
Powder Source	Compressed air (without water after filtering) 0.6x105Pa
Total Air Consumption	350L/min