



## *Automatic Blow Molding Machine (2000BPH)*



2000BPH two cavity blow molding machines are widely applied in blowing hollow plastic containers of various dimensions. They are characterized by stable quality of products, reasonable design of structure of machines, small size, low energy consumption, easy operation and convenient maintenance. All spare parts of two cavity automatic blow moulding machines are treated by high and new technologies, precise machining and careful assembly to attain technical requirements of all aspects. Moving parts are connected with boundary lubricating bearings and straight guide rails (guiding blocks are made in Japan). Japanese made bumper is adopted for preventing mechanical bumping, which ensures low mechanical noise, low failure rate and long service life. Moreover, unique design of air blowing mechanism ensures very high output rate of finished products. The operation of two cavity automatic bottle blowing machinery are computer controlled, which ensures accurate and reliable operation. Individualized operations and operation monitoring of the machine are realized by human-machine interface.

### **Technical specifications and dimensions:**

1. Production capacity: 1800-2000
2. Bottle blowing height: 50-350 mm
3. Max. mould thickness: 240mm
4. Machine capacity: 25KW
5. Power: 6-14 KW
6. Power source: 380V 3-phase /220 V 3-phase 50/60Hz
7. Working pressure: 0.7-0.9Mpa
8. Blowing pressure: 1.6-4.0Mpa
9. Overall dimension: 1908mm(L) × 1280mm(W) × 1800mm(H)