



Link-40H50 High Speed Fully Automatic Sealer Sealing Machine



Link-40H50 high speed unpacking machine introduced and absorbed foreign advanced technology, the use of CAM drive system and connecting rod combined control of the whole machine action, mechanical action fast, ready, stable, is the current domestic professional high speed unpacking machine. The machine is small in size, easy to operate, convenient to adjust, automatic warning to remind to add cartons, can be added at any time without stopping; Stop the machine with fault alarm and no doubt of damaging the carton. Exquisite appearance, compact, man-machine interface control, simple and convenient operation, the total length of the machine is 3120mm, the high-speed unpacking machine covers an area smaller than similar products. Double link double swing arm structure, light action, no vibration and no noise, folding more smoothly, and can make the carton length larger, 510mm. Double stopper design, can bear more, mainly according to the need to put down 4-5 cartons each time, will not produce pressure on the box, ensure that each carton is taken out, to ensure the success rate of the box.

The feeding mechanism of similar products on the market generally adopts the single pin way, and the carton is easy to bend the pin, so as to play the role of the box, produce pressure on the box, when the box can not be pulled out, affecting the success rate of the box.

Machine performance:

- * Equipment design and production line process and layout requirements, beautiful appearance generous, good manufacturing technology. Low power and water consumption, easy and fast operation, adjustment and maintenance;
- * The machine has good self-safety protection functions, such as overload protection and safety door, etc.
- * There is no tape automatic alarm function, with perfect mechanical, electrical protection and process protection function;

Storage mechanism: 80-90 unshaped cartons can be placed at one time (depending on the thickness of cartons), and can be supplemented at any time;

Technical Parameters:

| Model | Link-40H50 |
|--------------------------------|---------------------------------|
| Applicable to the power supply | 380V/ 50Hz /1.5KW |
| Work pressure | 6kgf /cm ² 450L/ min |
| Packing specification | 280≤L≤500;160≤W≤400;130≤H≤400; |
| | L+W≤900;220≤W+H/2≤600mm |
| Unpacking manner | Horizontal type |
| Countertop Height | 1050mm |
| Molding speed | 20~25 boxes/min |
| Packing tape | BOPP/PVC |
| Tape size | W48mm 60mm 75mm |
| Installation dimensions | L 2500 * W 1500 * 1910mm |
| The net weight | 1000Kg |