

WP-H series Vertical Packaging Machine



Application

- © Applicable Bag Type: pillow bag, gusset bag, seal type bag, triangle bag.
- © Applicable Film Material: a variety of laminated films, single layer PE film. Film thickness range 0.03~0.15mm.
- © Applicable Packing Materials: a variety of snack food, frozen food, milk powder, pet food, coffee, oatmeal, sugar, salt, puffed food, rice, herbal, tea, small hardware, etc.

Feature

- © PLC control, man machine interface, easy to operate and maintain.
- © Driven by double servo motors and optical tracking devices to keep high packing speed and high accuracy.
- © The frame of machine is made of stainless steel 304. equipped with auto-stop protection function when open the door.

Technical Parameters

Model	WP-H3220	WP-H4230	WP-H5235
Film Width	120~320mm	140~420mm	160~520mm
Bag Size	L: (40~210)mm	L: (40~330)mm	L: (40~350)mm
	W: (50~150)mm	W: (60~200)mm	W: (70~250)mm
Packing speed	95 (bags/min)	95 (bags/min)	90 (bags/min)
Film pulling driven	servo motor	servo motor	servo motor
Horizontal sealing driven system	servo motor	servo motor	servo motor
Voltage	3KW/220V/50(60)Hz	4.5KW/220V/50(60)Hz	4.2KW/220V/50(60)Hz
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.15m³/min	0.2m³/min	0.2m³/min
Machine Size(mm)	1326*1066*1503	1526*1266*1763	1716*1276*1768
Machine weight	400KG	580KG	660KG

Model	WP-H6240	WP-H7245
Film Width	200~620mm	230~720mm
Bag Size	L: (40~400)mm	L: (40~450)mm
	W: (90~300)mm	W: (105~350)mm
Packing speed	85 (bags/min)	80 (bags/min)
Film pulling driven	servo motor	servo motor
Horizontal sealing driven system	servo motor	servo motor
Voltage	5.0KW/220V/50(60)Hz	5.3KW/220V/50(60)Hz
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.2m³/min	0.2m³/min
Machine Size(mm)	1900*1400*1920	1996*1546*2188
Machine weight	750KG	930KG