



FL-5545TBA Automatic L Bar Sealers



L-bar sealing blades driven by cylinder provide the film bag with strong seams with one strike. Suitable for single or combined packing of ordinary products.

One-piece heat-resistant alloy blades, DuPont Teflon coated, anti-adhesive and easy to clean.

Packing size adjustable, no need to change module or bagging former.

Tunnel Technical Features

Stainless heating tubes and strong blowing motor ensure high heating efficiency, large air volume and uniform air circulation.

Solid metal rods wrapped by heat-resistance silicone tubes make the Conveyor rollers strong and resilient.

Scope of Application

Suitable for the packing demands of the mass production in industries such like software, food, cosmetics, printing, pharmaceuticals and floors, ceramics, beverage, hardware and so on.

Automatic Sealing And Shrinking Series Optional

Kissing Device HMI Safety Door Switch Transparent Material Detection Easy-to-tear Mouth.

Printed Film Detection S/S Machine Frame /Customized Painting Specific Electric/Pneumatic Brands.

Technical Parameters

Model	FL-5545TBA/TBB
Machine Dimensions (mm)	1700 X 840 X 1525
Max Packing Size (mm) L+H(mm) H<130	≤500
Max Packing Size (mm) W+H(mm) H<130	≤430
Sealing Size LxW (mm)	550 X 450
Capacity (pcs/m)	15~25
N.W. (kg)	225
Power (kw)	2.2
Power Source	1PH 220V 50/60Hz
Air Source (kg/cm ²)	6~8
Applicable Film	POF/PE