

Automatic Single Head ROCap Sealing Machine DARCS-60



Lorem Ipsum is simply dummy text of the printing and typesetting industry. Lorem Ipsum has been the industry standard dummy text ever since the 1500s, when an unknown printer took a galley of type and scrambled it to make a type specimen book. It has survived not only five centuries, but also the leap into electronic typesetting, remaining essentially unchanged.

Salient Features:

- No container No cap arrangement.
- Adjustable height of conveyor belt, to align with other machine of the line.
- SS elegantly matt finished body.
- Sealing pressure can be varied to suit different gauges and size of caps.
- Single motor synchronizes conveyor, star wheel, & platform turret.
- Adjustable bottle height gauge for easy and quick setting.
- Self-lubricating UHMW-PE guide profile for low friction wears surface, smooth and noiseless conveying.
- SS cladding or hard chrome plating of all exposed parts to ensure long life and resistance against corrosion.
- Synchronized A/C drives to synchronize, Conveyor, Star wheel and Platform turret & capping blow.
- Low noise level, low power consumptions

Specifications:

Model	DARCS-60
Output / Hour*	1000 to 3000 bottles.
Direction of Movement	Left to Right
No. of Sealing Head	1 Nos.
Fill Size ***	5 ml to 100 ml
Electrical Specification**	
Main Motor	1 HP / 415 Volts / 50 Hz.
Cap Feeding Bowl	300 Watt
Height of Conveyor**	860 mm to 910 mm