

Automatic Sachet Liquid Juice Energy Gel Packing Machine HY-YY50



It is suitable for automatic packaging of liquid paste products in daily chemical, food, health care and pharmaceutical industries, such as: mouthwash; energy drink, energy jelly, energy supplement, etc.; syrup, red ginseng drink, grain health cream, etc.

Features

- 1. Adopt high configuration: Siemens PLC controller and color touch screen operation; Taiwan AIRTAC cylinder; France Schneider switching power supply, etc.
- 2. Servo heat sealing bag, vertical sealing without stickers, exquisite bag type.
- 3. Material: The contact part of the box and material is made of SUS304, which is in line with GMP production.
- 4. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.
- 5. The equipment is equipped with casters for easy handling and movement.

Characteristics:

- 1. Rounded shaped sachet, the size of the nozzle can be designed to facilitate the extrusion of the liquid to prevent the liquid from spilling out.
- 2. Double metering head design, which can meet the automatic metering and packaging of viscous sauces and water-based products.
- 3. The punching die is made of HKS-9 material. After six processing techniques, it has high durability and long service life.
- 4. Add a disinfection lamp at the film pulling film to perform preliminary disinfection of the film.
- 5. Auxiliary equipment: feeding machine + coding machine + finished product conveyor + constant temperature mixing barrel.

Specification:

Model	HY-YY50
Filling Range	1-20/5-50/10-100ml
Sachet size	W: 25-100mm, L: 30-180mm
Max. Film Width	220mm
Sachet Type	Rounded back seal with easy tearing, longitudinal seal twisted edge seal
Filling Range	Pneumatic pump/magnetic pump
Capacity	20-45 ppm
Power Voltage and Consumption	220V50-60HZ/5.5KW
Air Pressure and Consumption	0.3m ³ /min, 0.6-0.8Mpa
Dimension (L*W*H)	930*1500*2400mm
Weight	400KG
Packaging Materials	PE laminated film, such as PET/AL/PE, PET/PE, Nylon/PE, etc.
	Thickness: 0.08~0.12mm (3 or 4 layers)
	Inner Core Diameter: 75mm
	Outer Roll Diameter: 300mm-500mm