



DXDO-K1200F High Speed Detergent Powder Four Side Sealing & Multi-line Packing Machine



Features:

- 1) Extremely efficient, high power, low noise, easy to maintain and has a long life span.
- 2) Roller heat sealing, four-side sealing, high speed multi-bag packing.
- 3) Easy to adjust, precise in measurement, requires a simple procedure for pouch length adjustment without changing the mould. Functions can be regulated for longitudinal sealing, transverse sealing, filling, notch cutting, longitudinal cutting, fracture line making and transverse cutting with the advanced technology for our man-machine interface.
- 4) Accuracy in page correcting, automatic counting and photoelectric tracking system is adopted to ensure the automatic correcting the double face printing design on packing bags.
- 5) Reliable performance, convenient to operate and fully automatic. A PLC is used for automatic control and a frequency changer makes speed adjusting even easier.
- 6) Applicable to a wide using: suitable for most of the complex film packing materials.

Usage:

It is suitable to pack materials in the fields of pharmacy industry, food industry and daily industry. Fill salt, pepper, sugar, oatmeal, soup, seeds, coffee, instant drinks and much more.

Technical Parameter:

Bag length	50-150mm(L) (adjustable)
Bag width	40-105mm(W)
Packing speed	30-50bags/min (4-10lines) depend on pouch size and material
Measuring range	1-80ml
Cutting fashion	Flat cutting
Sealing fashion	4 side sealing
Applicable film	PET/AL/PE PET/PE NY/AL/PE NY/PE
Max width of film roll	1200mm
Max film roll diameter	Φ300mm
Film roll core diameter	Φ75-76 mm
Power voltage	380V/ 3 phase 4 wires 50HZ
Power	15KW
Package size	(L)1650mm×(W)1500mm×(H)2200mm
G.W	1800KG