

XHL-HXG4 Liquid Filling Equipment For Glass Bottle



HXG automatic rotary capping machines has the function of auto pick and place cap, with invariable capping torque application, advantage of stable placing cap, and high capping quality. The bottles are continuously infeed to starwheel, more stable and fast. It is widely used in the industry of pharmaceutical, foodstuff and chemical etc.

Features

- Auto cap pick and place, more stably, no oblique.
- Magnetic moment cap rotating, moment may be adjusted freely, high yield of capping.
- Continuous operation, bottle feeding and exiting.
- Rotary operation mechanism, more efficient, centralized lubricaiton system, smooth and reliable.
- PLC control system, no bottle no outer cover, with line protection system.

Technical Parameters:

Items	HXG/4	HXG/6	HXG/8	HXG/12	HXG/18
Applicable bottle size	Φ20-Φ15mm				
Cap size range	Φ12-Φ70mm				
Production capacity(100ml)BPM	60-80 BPM	80-100 BPM	100-130 BPM	130-160 BPM	160-210 BPM
Yield of capping	≥99%				
Power supply	220/380V 50Hz				
Power consumption	≤2kw				
Air pressure range	0.4 - 0.6 MPa				
Speed control	Frequency conversion adjustable speed				
Single machine noise	≤70dB				
Net weight	2000kg				
Overall dimensions(mm)	2000(L)*1100(W)*1600(H) mm				