

## *Potato Chips Packing Machine ZG8-250*



Suitable for metering of all kinds of granule, flake, strip, round and irregular products such as sunflower seeds, peanuts, coffee beans, chocolate, nuts, dried fruit, apple chips, banana chips, potato chips, biscuit, candy, fruit, vegetable salad, noodles, quick-frozen food, puffed food, pet food, seed, hardware and plastic granule.

Suitable for bag type such as 4 sides sealing bag, 3 sides sealing bag, doypack, slant spout bag, zipper bag, paper bag.

IAPACK is one of the top level China automatic nuts doypack packing machine with zipper manufacturers and suppliers, we are always able to provide customers with cheap automatic nuts doypack packing machine with zipper products. Welcome to buy low price products from us.

### **Function and characteristics:**

1. Easy to operate, adopt advanced PLC from Germany Siemens, mate with touch screen and electric control system, the man-machine interface is friendly.
2. Frequency conversion adjusts the speed: this machine uses frequency conversion equipment, can be adjusted within the range according to the needs of reality in production.
3. Automatic checking: no pouch or pouch open error, no fill, no seal. the bag can be used again, avoid wasting packing materials and raw materials.
4. Safety device: Machine stop at abnormal air pressure, heater disconnection alarm.
5. Horizontal conveyor style to giving bag: it can put on more bags on the bag storage and have a low requirement about the quality of bags.
6. The width of the bags could be adjusted by electrical motor. Press the control-button could adjust the width of clips, easily operate, and save time.
7. It matches with the glass safety door. The machine will stop working when you open the door. So that it could protect the safety of operators. At the same time, it could prevent dust.
8. Use the plastic bearing, don't need put on oil, less pollution.
9. Use no oil vacuum pump, avoid polluting the environment in the production.

10. The packing materials loss low, what this machine is used the preformed bag, the bag pattern is perfect and has a high quality of the sealing part, this improved the product specification
11. Product or packing bag contact parts adopt stainless steel or other materials which accord with the food hygienic requirements, guarantee hygiene and security of the food
12. With different feeders changed to pack solid, liquid, thick liquid ,powder and so on.
13. The packing bag suits in extensive range, suit for multi-layer compound, monolayer PE, PP and so on Preformed bag made by film and paper
14. Working process of this 8-working position machine is giving bags-coding date-opening bags-filling 1st-filling 2nd & vibrating-reserve-exhausting and sealing-forming & output packaging. Full-automatically(suitable for stand-up pouch with zipper or spouted)
15. Working process of this 6-working position machine is giving bags-coding date-opening bag-filling&vibrating-exhausting and sealing-forming& output packaging. Full-automatically(suitable for flat bags and normal stand-up pouches)

### 10-head weigher/14-head weigher

1. it can apply in: Dry & Processed Foods, Fresh Foods. Fox example: Sank Foods, Seeds(Pulses), Coffee(granules/beans), Tea, Sugar, Grated Cheese, Bakery Products, Candies & Confectionery, Rice, Nuts & Dried Fruits, Spices, small Pasta pieces, Pet Food(pellets) etc.
2. Use the digital sensors to enhance speed, precision and anti-jamming capability.
3. Optional language of operation. English, Japanese, Chinese, Italian, German, Spanish, Russian etc
4. Frame with IP65 protection
5. Statistical Data-Inspect on screen and via optional printer output
6. Options: Dimpled plate on all product contact surfaces, Overweight discharge equipment, Collection hopper, Printer.

### Bucket elevator (Include Feeder)

This kind of elevator is used mainly to convey the solid food ,such as rice, chip potato ,candy ,etc. it composes the automatic quantitative packing system combined with the weigher and packing machine, which is applying widely. Be made of 304 stainless steel and plastic (PP) which is hygienic and healthy .the elevator is controlled automatically.

Working platform: carbon steel

### Technical Parameters:

Model	ZG8-200	ZG8-250	ZG8-300
Working position	eight-working position		
Pouch material	Laminated film ,PE,PP		
Pouch pattern	stand-up pouch,flat bag		
Pouch size	W:100-210mm L:100-350mm	W: 150-260mm L:150-350mm	W:200-300mm L:200-450mm
Filling range	10-1000g		
Measuring way	Multi-head weigher		
Weight Accuracy	±0.1-2g		
Speed	10-60bags/min	8-35bags/min	8-30bags/min
Voltage	380V 3phase 50HZ/60HZ		
Total power	4kw	4.5kw	6.5KW
Compress air	0.6m3/min(supply by user)		
Weight	1200kgs	1400kgs	1500kgs