



## JB-6000 Aseptic Brick Carton Aseptic Filling Machine



It applies to sterilization by liquid UHT milk and a variety of non-carbonated drinks, fruit juice, coffee, plant protein drinks, tea drinks, wine etc. gravity of aseptic packaging of liquid food, the machine uses all stainless steel materials, core components All of a world-class brand, auto-complete feed, sterilization, filling, forming, packaging in the form of paper aluminum composite brick.

### Parameter:

Model	JB-6000
Name	Aseptic brick filling machine
Capacity	6000 packs per hour
Filling capacity	100 ml, 125 ml, 160 ml, 200 ml, 220 ml, 250 ml,
Dimension	4690×2540×3760mm
Connect	2200 mm (W) × 3500 mm (H)
Total Weight	5000 kg
Electrical	380V±10 % ( 3φ) 50/60Hz
the total power	35 KW
Air consumption	500±100 L/Min ( 0.6~0.7 MPa) ;Connect: Thread 1/2"
Tap water consumption	15 L/M ( 0.3~0.45 Mpa; ≤ 20°C );Thread 1/2"
Steam consumption	4.5 kg/H ( 130 ± 5 °C、0.17± 0.03 Mpa) ;Connect:DN25
H2O2 consumption	0.6~ 1.0 L/H ( 30~50 %)
Control system	PLC man-machine interface
Discharge conveyor	chain
Filling temperature	5°C~50°C
Filling Numbers	1
Packaging forms	paper - aluminum composite bricks aseptic brick shape
Sterile package shelf life	the paper aluminum composite film, under normal temperature 25 °C ~ 30 °C, Shelf life is 6 months or more
Access to the air pressure	0.8 Mpa