

Automatic Horizontal Packaging Machine For Broccoli / Lettuce KW750



It is the result of the convey commitment with innovation and the technological development. This ongoing process brings us a new family of machines with an improved performance and much more ease of use. Only simple PLC and vegetable position adjustment avoiding cutted.

The new machine features all the strength, reliability, and operation easiness of the CONVEY machines. Added to these well-known characteristics of CONVEY, the new model also features a higher flexibility and versatility (as the sealing head is powered with an independent motor), together with a much easier operation thanks to its touch screen control panel.

The great flexibility, proven reliability and the innovative technology applied to the new CONVEY machine. It is the ideal packaging machine for a very wide range of applications in the food industry and specially in the produce, vegetable, meat, cheese,... sectors.

Technical features:

- Electronic packaging machine powered with independent motors synchronized electronically.
- Machine is built on a iron steel frame in a painting execution
- Middle sealing could be adjustable from 0-200mm to allow different size to pass through
- The sealing head is equipped with an independent motor that provides a very high flexibility as it allows optimizing the cycle time and also to produce minimum length packs.
- Holder that eases the load of heavy rolls. It is equipped with motorized film unwinding system for the optimum machine work.
- In-feed conveyor 2.5 meters long fully V-adjustable belts made in aluminum foil.
- The touch screen control panel allows a simple and very intuitive access to the machine parameters. It allows various parameter settings for each product (bag length, speed, etc...).
- The “No product - No Bag” and “Misplaced product safety” functions are standard in this machine.

Technical Parameter:

Weight	About 1300kgs
Sealing system	top sealing
Product range	vegetable&herbs&fruits as well as other regular products
Bag dimensions	(Length) \geq 100mm*(width)70-300mm*(highness)50-200mm
Capacity	10-45 packs/min
Power supply	4kw(220V,50/60HZ)
Machine dimension	2500*800*1600mm
In-feed dimension	3000*400*1000mm
Film size	750mm width ,0.025-0.060mm thickness