

S-5647-BX-SH-MAP Shrink Packaging Machine - With MAP



Hermetic Sealing with barrier shrinkable film and gas flushing for Modified Atmosphere Packaging (MAP) is an ideal wrapper for fresh fish packaging to achieve longer shelf life.

Features

- 3 axis servo motor for in-feed, center sealing and end sealing.
- Hermetic box motion end sealing.
- Yaskawa motion controller.
- Shinko P.I.D. temperature control modular.
- User-friendly 10.4" colorful touch screen.
- 100 sets products data memories for items change-over quick and easy.
- Overload protection for end sealer with auto disengage function.
- Top brush belt makes the items transfer smoothly at high running speed.
- Dancing roller and motorized film feeding roller make the film supply tension stable.
- With sucking transfer belt for easy & safe operation.
- Precise pin perforator makes the package surface perfect.

Specification

Model No.	S-5647-BX-SH-MAP	S-5661-BX-SH-MAP
Capacity (PPM)	30 ~ 60	20 ~ 50
Bag Length (mm)	70 ~ 450	130 ~ 500
Max. Film Width (mm)	470	610
Max. Product Width (mm)	190	265
Max. Product Height (mm)	75	120
Electricity for Wrapper (mm)	5.5 Kw - AC-220 / 380 Volt - 3 phase + Ground	
Electricity for Tunnel	16 Kw - AC 380 Volt - 3 phase + Ground	