

DPB-250 PVC Flat Plate Automatic Blister Packing Machine for Capsules/ Tablets/ Pills



Feature:

- 1. Machine-tool track type of casting machine-base, taken these processing like backfire, maturing, high benchmark and without distortion.
- 2. Each box of section processed through professional, equipment, to assure high precision and good interchangeability.
- 3. Forming, sealing, indentation etc. All parts could be easily adjusted on the track with triangle string and flat string, strong applicability. Small oversize, save installation space.
- 4. Reducer adapts parallel-axes bevel wheel, to avoid loose and smooth between chain or strap when it is driving.
- 5. Stroke can be adjust freely, widely used ease of operation, stable running.
- 6. Mould located by male pin, ease and accuracy of changing mould. Product any sizes and shapes of strip by changing the mould on the same machine, and it also can pack for liquid if liquid filling device equipped. It is multipurpose machine.
- 7. It adapts up and down net pattern concave-convex to conjugate, multilevel air cylinder, double-heat sealing, good sealing quality.

Purpose:

- It is the newest high precision capsules and pills/tablets packing machine in current pharmacy industry.
- It is widely used for capsule, tablet, honey pills in pharmaceutical industry, for milk tablet, candy, chocolate in food industry, for injector, syringes, pins, small component ect. In electron or hardware industry as all kind of shapes of ALU-ALU, ALU-plastic, paper-plastic combined packing.

Technique parameters

Model No	DPB-250	DPB-320
Punch Frequency (Times/Min)	6-60	8-35
Production Capacity (Blister/hour)	9600-12000 (Standard	12000-15000 (Standard
	80*57)	80*57)
Max Forming Area & Depth (mm)	Standard 250*110*10	Standard 310*110*10
	Max 250*200*50	Max 310*200*50
	25 times / min	25 times / min
Stroke (mm)	20-120	20-120
Standard Blister Size (mm)	80*57, 80*35, 95*65, 105*42, 105*55 (customized)	
Air Supply	0.5-0.8 MPa 0.15 CBM/min	
Total Power	6 KW	6 KW
Voltage	220/380 V 50 Hz	220/380 V 50 Hz
Main Motor Power	1.5 KW	1.5 KW
PVC Thickness (mm)	0.15-0.5*260	0.15-0.5-320
PTP Aluminum Foil Thickness	0.02-0.035*260	0.02-0.035*320
Dialysis Paper (mm)	50-100 g/m2*260	50-100 g/m2*320
Mould Cooling	Cold Water	
Dimension (mm)	3000*720*1600	3000*780*1640
Weight (KG)	1700	1900