



BD-26 Automatic Pillow-Bag Packing Machine



BD-26 Automatic Pillow-Bag Packing Machine. Tablet Packing Machine. Automatic packaging machine which vertical, Intermittent operation, flat bag (3-side sealing, 4-side sealing) and pillow-bag style, can perform the whole process of bag-making, measuring, filling, sealing, cutting, printing the batch number, counting and photoelectric tracing automatically. With the features of beautiful looking and easy operation, the top-quality industry Aluminum-alloy is adopted as the machine shelf. The position of the new-designed integrative electric cutter can be adjusted optionally during running. It can not only avoid the bag-blocking, but also prolong the life span of the cutter. It is convenient for the customers to adjust. Two-shaft driving rotary arm takes place of the traditional single-shaft driving rotary arm to avoid the transformation of the single one while overburdened. It improves the quality of packaging effectively. The new structure of bi-bag-pulling wheel is adopted, which not only guaranteed the exactitude of bag pulling but also the smoothness of the bag. Adopts CPU to control each function state, and set up the man-machine conversation interface. The double channel temperature of the horizontal and vertical is controlled by intelligent temperature controlling device. Intelligent photo cell orientation, transform discretionarily between the light/shade. Strongly anti-jamming, when three bags can't catch up with the upper mark the machine will stop and give an alarm. The packaging speed can be adjusted continuously within specified range. Designed the stop-position specially in order not to make the wrapping material burnt. Measurement adopts adjustable cup method which is accorded with the measurement standard. The measurement of material with even density is exact. Optional devices: The above machine may be changed into 4-side-sealing and equipped with hot stamp imprinting machine. It is choice to be hackle cutters, point line cutters, easy-tearing cutters and exhaust. It is choice to be both heat-sealing mechanism and net or even heat-sealing channel veins. The machine that has special bag-size or measuring requirement can be devised and produced specially.

Technical Parameters:

Model	BD-26
Production Capacity	40-60 bag/min (depend on the material and specifications)
Measuring Range	10-50 ml
Bag Size	(L) 50-140, (W) 50-100 mm
Wrapper	Various Laminate Film
Wrapper Diameter	≤ 300 mm
Temperature	0-40 °C
Humidity	20-90 % RH
Working Condition	No Caution, Flammable / Explosive Gas Or Powder
Power	380V,50Hz,1.1Kw
Packing Size	800*600*1700 mm
Packing Weight	250 Kg