

UN-280ZS Flow Wrapper, HFFS Wrapping Machine



The UN-280ZS flow wrapper is the shrink version of the UN-580ZS. The maximum film width is 300mm. It is an economic multi-functional HFFS wrapping machine.

Adopting the low film packing method, the UN-280ZS flow wrapper is suitable for the packaging of piece parts, goods with water and other irregular products. The production capacity is 50-190 bags/min. The bag length is 150-450mm, and the width is 25-110mm.

Suitable for solid products such as hamburgers, instant noodles, bread, mechanical parts, and more.

Feature

1. Low film packing machine. The film covers the products from bottom to the top, this packing method can prevent small and loose parts from falling.
2. The low film packing machines produce packages with better air tightness. It can avoid the attachment of foreign matter on the vertical sealing position, and then avoids air leakage or tears.
3. Equipped with an automatic inspection device. The length of the packing bag can be adjusted in the packaging process.
4. Equipped with a rotating cutting head. The cutting operation and packaging operation proceed simultaneously, which improves production efficiency greatly.

Main Specification

| | | | | |
|------------------------------------|-----------------------|-----------|----------|----------|
| Production capacity | 50-190 bags/min | | | |
| Range of packaging | Bag length | 150-450mm | 70-260mm | 30-130mm |
| | Width | 25-110mm | 25-100mm | 25-80mm |
| | Height | < 50mm | < 50mm | < 50mm |
| Maximum diameter of packaging film | Ø350mm | | | |
| Maximum width of packing film | 300mm | | | |
| Total power | 3Kw | | | |
| Power supply | 220V 50-60Hz | | | |
| Total weight | 750kg | | | |
| Dimensions | 3200-4700*1050*1450mm | | | |