



Automatic Quantitative Filling and Packaging Machine JS-12



Product Features:

- This machine is built with double hopper loaders for material mixing purposes. Three hopper loaders are available upon request.
- The machine is built with 2 hoppers for mixing different materials.
- Machine equips with photo-cell device ensure accurate bag forming, sealing and cutting performances.
- This unit can perform three sides sealing, four sides sealing or pillow type packaging. Specify desired packing choice when ordering.
- Equipped with a product counting device.
- All components in direct contact with the product are made of stainless steel, conforming to sanitary standards.
- Convenient package size & packing speed are adjustable. Adjustment can be made while the machine is running.
- The entire procedure from weighing, bag forming, filling and sealing to cutting and packaging is fully automatically operated.
- Machines can be made to customers' own specifications on request.
- 3 hopper or more are available upon request.
- Machine can equip vibration loading system with agitator for hard-flow packaging products.

- Applicable packing products: Powders, granules, tablets... etc... such as sugar, salt, pepper, tea , coffee, medicine, peanuts, melon seeds, spices, heath foods...etc.
- Applicable packing materials: Poly-Cello. PET+PE+Aluminum Foil+PE,OPP+PE, Aluminum Foil+PE and other heat sealable materials.

- Standard Equipment: Tool box containing: 1 x Box wrench. 1 x Hexagonal Wrench. 1 x Screwdriver.
- Optional Equipment: Automatic quantity warning device. Automatic Date Coder. Easy opening device. Input conveyor & Output conveyor.

Specifications:

Packaging type (One option only)	3 sides sealing, 4 sides sealing or pillow type packaging
Packaging weight	1-60g (varies with product density)
	(weight up to 100g available)
Packaging size	Film width (W)40-160mm or 80-240mm
	Bag length (L)50-110mm or 70-180mm (Other size are available upon request)
Packaging speed	About 20~100bags/min
Motor	1/4 HP (Main drive)
Power supply	110/220V, 50/60HZ single phase (can be made upon request)
Machine dimensions (L x W x H)	135 x 100 x 200 cm (Approximately)
Packing dimensions (L x W x H)	155 x 112 x 224 cm (Approximately)
Net weight	450 kgs
Gross weight	600 kgs