

SA-313 POF Shrink Tunnel (mini Type)



From table type to high production type, the wide range of TAYI YEH shrink packaging machines are quality designed and engineered to give extraordinary performance.

Features

- Machine constructions use S-41 steel material.
- Machine frames formed up by model.
- Specified spare parts kit.
- Live roller rod conveyor.
- Speed changeable motor with speed desired & adjusted easily.
- Fully re-circulating heating air.
- Highly efficient heating up with good separations.
- Temperature controlled automatically.
- Temperature variable with easily operation.
- SUS thermocouple systems.
- SUS 304 stainless steel inner tunnel.
- SUS 304 stainless material wires & terminals, covered with ceramic guards.
- CE model availale.

Specification

MODEL	CHAMBER	OVERALL	PACKAGE	CONVEYOR	POWER	CONSUMPTION
	ММ	(L x W x H) MM	(W x H) MM	SPEED (MPM)		KW
SA-312 PVC	550*350*100	1000x650x500	300x120	0-5	220V	4.5
SA-313 PVC	800x400x200	1265x720x1200	340x170	0-7	220V / 380V	0
SA-313 POF			300x130			9
SA-316 PVC	1200x400x250	1865x720x1450	340x230	0-8	220V / 380V	14
SA-316 POF			300x170			
SA-316 POF-L	2000x400x250	3065x720x1450	300x170	0-8	220V / 380V	25
SA-317 PVC	1200x500x300	18650x820x1500	420x270	0-8	220V / 380V	19
SA-317 POF			380x220			19
SA-317 POF- L	2000x500x300	3065x820x1500	380x220	0-8	220V / 380V	22
SA-318 PVC	1200x600x350	1800x920x1550	510x330	0-8	220V / 380V	21
SA-318 POF			460x260			
SA-318 POF- L	2000x600x350	3065x920x1550	460x260	0-8	220V / 380V	28
SA-319 PVC	1500x700x400	2465x1020x1650	595x350	0-8	220V / 380V	24
SA-319 POF			550x300			
SA-319 POF-L	2000x700x400	3065x1020x1650	550x300	0-8	220V / 380V	30
TY-37J POF	1600x500x300	2000x960x1140	380x220	0-25	220V / 380V	18
TY-50J POF	1500x500x300	2090x820x1590	300x150	0-25	220V / 380V	18

^{*} Specifications Subject to change without prior notice.

Applications

Suitable for food, gifts, hardware, daily-use products, electronics, electrical industries, medicines, bamboo ware...etc.

^{*} Production capacity is subject to product size, type of product, shrink film material and shrink film thickness.

^{**} Specifications are subject to change without prior notice.