

VD-6_FOTT Automatic Filling Machine



This automatic filler is designed to fill liquid, semi liquid, viscous (paste) and products with particles into the glass and jars & bottles.

TECHNICAL SPECIFICATIONS

- * This high speed filler is a mono block system including the filling, cap sorting and capping .It gives economical solutions to the middle sized companies.
- * VD-6 OT consists of 3 parts. Filling part, cap sorting part and capping part.
- * Works with volumetric piston system.
- * Works with oil-free pneumatic system.
- * According to cap types the sorting mechanism can be vibratory sorter, elevating sorter or mechanical system.
- * Touch Panel Control System
- * Rotary cap sorting, index table system
- * PLC Stainless Steel control system

MATERIALS USED ON THE FILLER

* The parts that contact with the product are 316 L stainless steel. The other parts are aluminum and 304 L stainless steel.

OPERATING TEMPERATURE: +5 º /+90 º

FILLING ACCURACY: ± %1

Model	Minimum Filling Range (ml)	Maximum Filling Range (ml)	Filling Pistons	Capacity (Packages / Hour)
VD 50-6_FOTT	5 ml	50 ml	6	5000 Packages / Hour
VD 150-6_FOTT	15 ml	150 ml	6	4500 Packages / Hour
VD 500-6_FOTT	50 ml	500 ml	6	3600 Packages / Hour
VD 1000-6_FOTT	100 ml	1000 ml	6	2500 Packages / Hour
VD 2000-6_FOTT	200 ml	2000 ml	6	2000 Packages / Hour



